



Features & Benefits

- Easy to install
- Simple cable management
- Suitable for Gigabit Ethernet applications
- Adjustable recessed mounting version available
- Mix and match copper and fibre in one panel
- Manufactured in the UK

Specification

Width	483mm (19")
Depth	95mm
Height	1u (44mm)
Fixing Centres	467mm
Material	Mild steel sheet CR4 to BSEN 10130-1999 DC01
Finish	Matt black polyester paint
Socket Labels	Write-on silk screen on panel front
Cable Management	Improved cabling facility with easy to use cable tie positions for left and right cable entry
	Colour coded to T568B
IDC Labelling	Industry standard 4 way IDCs
IDC Blocks	ANSI/TIA-568-C Category 6 Specification
Conforms to	ANSI/TIA-568-C Category 6 Specification

Ordering Information

Product Description	Part Number
Cat 6 24 Way High Density 2020 Panel	009-001-001-40

The Connectix 2020 Series Patch Panel is an alternative to the Category 6 High Density Panel. It offers the same Category 6 performance as the standard panel but has been designed to present the cable termination IDCs horizontally on a tray at the rear, making termination and cable management easier.

Category 6 High Density 24 way panels achieve optimum transmission performances by incorporating the highest quality components and innovative on-board compensation techniques.

This panels offer extended PowerSum characteristics and exceeds the ANSI/TIA-568-C specifications. When combined with Connectix Category 6 Modules and UTP Cable the link will perform well in excess of the Category 6 specification.

LC, SC, ST and FC fibre modules are also available, complete with a Starlight compatible gland hole and integrated management tray. Blank modules can be included for future expansion.

