

Available
January 2018



E6TM PRO

Up to 103 lm/W
TOOL-FREE installation




Record breaking
installation times when
using the RapidWire
connection system



INSULATION COVERABLE 300mm FIBRE BASED

- No accessory required
- No fire cage or hood required
- No insulation cut-out required

INTEGRATED DRIVER WITH
LATCHING LOOP IN/LOOP
OUT TERMINALS SUITABLE
FOR USE WITH SOLID OR
STRANDED CABLE



NEW AND IMPROVED
LATCHING TERMINALS
FOR FASTER INSTALLATION



FIRST FIX & TESTING



SECOND FIX

Description

The brand new E6™ PRO is a revolution in LED downlight performance and installation. Utilising the unique RapidWire connection system, the whole product can be fully wired and installed in a matter of seconds. The use of latching terminals provides the security of screw terminations for both solid and stranded core cables and can be wired even faster than standard push fits. The removable connector allows full circuit insulation resistance testing without risking any damage to the downlight, which can be simply plugged in afterwards.

6W up to 620 Lumens

L70 50,000 Hours



FOR DIMMING COMPATIBILITY SEE PAGE 154



FIXED E6™ PRO
IP65 WITH THE
APPROPRIATE
BEZEL (SOLD
SEPARATELY)



EN-DE6PRO

E6™ PRO Fixed 6W Dimmable
Fire Rated LED Downlight



Cat. No.

Watts

Beam

Colour

Lumens

lm/W

L70 Life [hrs]

Overall [Ø]

Cutout [Ø]

Recess

Subst.

EN-DE6PRO DIMMABLE FIXED

EN-DE6PRO/30	6W	60°	3000K	580lm	97	50,000	85mm	70mm	100mm	50W
EN-DE6PRO/40	6W	60°	4000K	620lm	103	50,000	85mm	70mm	100mm	50W


ACCESSORIES

EN-BZE8* E6™ PRO/E8™ Fixed IP65 Aluminium Downlight Bezel


*Add suffix **W, MW, PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes.

3 hour **Emergency pack AU-FRLM10EM** available.

Finish Options:



Technical Information



(RD) 100mm Recess Depth
(OD) 85mm Overall [Ø]

